

Map Unit Symbol	Map Unit Name	Component Name	Percent of Map Unit	Depth to Seasonal High Water Table (inches)	Seasonal Flooding Frequency	Limitations for Buildings without Basements	Limitations for Sewage Lagoons	Permeability Class	Runoff Class
1	AGUA FRIA LOAM								
		AGUA FRIA	75	> 72	None	Not limited	Very limited	Moderately slow	Medium
10	BAYFIELD SILTY CLAY LOAM, 1 TO 3 PERCENT SLOPES								
		BAYFIELD	75	> 72	None	Very limited	Somewhat limited	Slow	High
11	BAYFIELD SILTY CLAY LOAM, GULLIED, 1 TO 3 PERCENT SLOPES								
		BAYFIELD, GULLIED	75	> 72	None	Very limited	Somewhat limited	Slow	High
12	BAYFIELD SILTY CLAY LOAM, SEEPED, 1 TO 3 PERCENT SLOPES								
		BAYFIELD, SEEPED	75	15-72	Occasional	Very limited	Very limited	Slow	High
13	BIG BLUE CLAY LOAM								
		BIG BLUE	90	9-72	Occasional	Very limited	Very limited	Slow	High
14	BODOT CLAY, 3 TO 10 PERCENT SLOPES								
		BODOT	75	> 72	None	Somewhat limited	Very limited	Slow	Very high
15	BOROHEMISTS, PONDED								
		BOROHEMISTS, PONDED	100	6-72	Occasional	Very limited	Very limited	Slow	Medium
16	BUCKLE LOAM								
		BUCKLE	75	> 72	None	Somewhat limited	Somewhat limited	Moderately slow	Medium
17	CHRIS VERY STONY LOAM, 9 TO 25 PERCENT SLOPES								
		CHRIS	80	> 72	None	Very limited	Very limited	Slow	Very high
18	CLARK FORK VERY COBBLY SANDY LOAM								
		CLARK FORK	90	> 72	None	Very limited	Very limited	Moderately rapid	Very low
19	CLAYBURN LOAM, 3 TO 12 PERCENT SLOPES								
		CLAYBURN	75	> 72	None	Somewhat limited	Very limited	Moderately slow	High
2	ALAMOSA LOAM								
		ALAMOSA	75	15-72	Frequent	Very limited	Very limited	Moderately slow	Medium
20	CLAYBURN COBBLY LOAM, 6 TO 25 PERCENT SLOPES								
		CLAYBURN	80	> 72	None	Very limited	Very limited	Moderately slow	High
21	CONI LOAM, 4 TO 25 PERCENT SLOPES								
		CONI	75	> 72	None	Very limited	Very limited	Slow	Very high
22	CORTA LOAM, 1 TO 3 PERCENT SLOPES								
		CORTA	75	> 72	None	Very limited	Somewhat limited	Very slow	Very high

Map Unit Symbol	Map Unit Name	Component Name	Percent of Map Unit	Depth to Seasonal High Water Table (inches)	Seasonal Flooding Frequency	Limitations for Buildings without Basements	Limitations for Sewage Lagoons	Permeability Class	Runoff Class
23	CORTA LOAM, 3 TO 8 PERCENT SLOPES								
		CORTA	80	> 72	None	Very limited	Somewhat limited	Very slow	Very high
24	DULCE-TRAVESSILLA-ROCK OUTCROP COMPLEX, 6 TO 50 PERCENT SLOPES								
		DULCE	40	> 72	None	Very limited	Very limited	Moderate	High
		TRAVESSILLA	25	> 72	None	Very limited	Very limited	Slow	Very high
		ROCK OUTCROP	25	> 72	None	Very limited	Very limited	Very slow	Very high
25	DURANGO COBBLY LOAM, 3 TO 20 PERCENT SLOPES								
		DURANGO	80	> 72	None	Somewhat limited	Very limited	Slow	High
26	FALFA CLAY LOAM, 1 TO 3 PERCENT SLOPES								
		FALFA	80	> 72	None	Very limited	Somewhat limited	Slow	High
27	FALFA CLAY LOAM, 3 TO 8 PERCENT SLOPES								
		FALFA	80	> 72	None	Very limited	Somewhat limited	Slow	Very high
28	FLUVAQUENTS, SANDY, FREQUENTLY FLOODED								
		FLUVAQUENTS, FREQUENTLY FLOOD	95	27-72	Frequent	Very limited	Very limited	Moderately rapid	Very low
29	FORTWINGATE STONY FINE SANDY LOAM, 3 TO 12 PERCENT SLOPES								
		FORTWINGATE	75	> 72	None	Very limited	Very limited	Slow	High
3	ANVIK LOAM, 12 TO 45 PERCENT SLOPES								
		ANVIK	80	> 72	None	Very limited	Very limited	Moderate	High
30	FORTWINGATE-ROCK OUTCROP COMPLEX, 6 TO 25 PERCENT SLOPES								
		FORTWINGATE	45	> 72	None	Very limited	Very limited	Slow	High
		ROCK OUTCROP	35	> 72	None	Very limited	Very limited	Very slow	Very high
31	GOLDVALE VERY STONY FINE SANDY LOAM, 15 TO 65 PERCENT SLOPES								
		GOLDVALE	85	> 72	None	Very limited	Very limited	Moderately slow	High
32	HAPLOBOROLLS-RUBBLE LAND COMPLEX, 10 TO 60 PERCENT SLOPES								
		HAPLOBOROLLS	40	> 72	None	Very limited	Very limited	Moderate	High
		RUBBLE LAND	40	> 72	Not Rated	Very limited	Very limited	Very rapid	Negligible
33	HARLAN COBBLY LOAM, MOIST, 1 TO 3 PERCENT SLOPES								
		HARLAN, MOIST	80	> 72	None	Not limited	Very limited	Moderate	Low

Map Unit Symbol	Map Unit Name	Component Name	Percent of Map Unit	Depth to Seasonal High Water Table (inches)	Seasonal Flooding Frequency	Limitations for Buildings without Basements	Limitations for Sewage Lagoons	Permeability Class	Runoff Class
34	HARLAN COBBLY LOAM, MOIST, 3 TO 15 PERCENT SLOPES								
		HARLAN, MOIST	85	> 72	None	Somewhat limited	Very limited	Moderate	Medium
35	HAYNESS LOAM, 1 TO 3 PERCENT SLOPES								
		HAYNESS	95	> 72	None	Not limited	Somewhat limited	Moderate	Low
36	HAYNESS LOAM, 3 TO 12 PERCENT SLOPES								
		HAYNESS	95	> 72	None	Somewhat limited	Very limited	Moderate	Medium
37	HERM LOAM, 6 TO 25 PERCENT SLOPES								
		HERM	80	> 72	None	Very limited	Very limited	Slow	Very high
38	HERM VARIANT CLAY LOAM, 2 TO 8 PERCENT SLOPES								
		HERM VARIANT	80	> 72	None	Somewhat limited	Somewhat limited	Slow	Very high
39	HESPERUS LOAM, 3 TO 12 PERCENT SLOPES								
		HESPERUS	75	> 72	None	Somewhat limited	Very limited	Moderate	Medium
4	ARBOLES SILTY CLAY LOAM, 0 TO 3 PERCENT SLOPES								
		ARBOLES	85	> 72	None	Very limited	Somewhat limited	Slow	High
40	HORSETHIEF VERY STONY FINE SANDY LOAM, 20 TO 65 PERCENT SLOPES								
		HORSETHIEF	75	> 72	None	Very limited	Very limited	Moderately slow	High
41	LAZEAR STONY LOAM, 6 TO 25 PERCENT SLOPES								
		LAZEAR	85	> 72	None	Very limited	Very limited	Slow	Very high
42	LAZEAR-ROCK OUTCROP COMPLEX, 12 TO 65 PERCENT SLOPES								
		LAZEAR	50	> 72	None	Very limited	Very limited	Slow	Very high
		ROCK OUTCROP	30	> 72	Not Rated	Very limited	Very limited	Very slow	Very high
43	LEADVILLE VERY STONY SANDY LOAM, 15 TO 55 PERCENT SLOPES								
		LEADVILLE	55	> 72	None	Very limited	Very limited	Moderate	High
44	MIKIM LOAM, 3 TO 12 PERCENT SLOPES								
		MIKIM	80	> 72	None	Somewhat limited	Very limited	Moderate	Medium
45	NEHAR STONY SANDY LOAM								
		NEHAR	75	> 72	None	Very limited	Very limited	Slow	High
46	NORDICOL VERY STONY SANDY LOAM, 6 TO 25 PERCENT SLOPES								
		NORDICOL	75	> 72	None	Very limited	Very limited	Moderate	Low
47	NUTRIOSLO LOAM								
		NUTRIOSLO	80	> 72	None	Not limited	Somewhat limited	Moderate	Low

Map Unit Symbol	Map Unit Name	Component Name	Percent of Map Unit	Depth to Seasonal High Water Table (inches)	Seasonal Flooding Frequency	Limitations for Buildings without Basements	Limitations for Sewage Lagoons	Permeability Class	Runoff Class
48	PANITCHEN-DOMINGUEZ VARIANT SILTY CLAY LOAMS								
		PANITCHEN	50	> 72	None	Not limited	Somewhat limited	Moderately slow	Medium
		DOMINGUEZ VARIANT	35	> 72	None	Somewhat limited	Somewhat limited	Slow	High
49	PASTORIUS COBBLY LOAM								
		PASTORIUS	80	> 72	None	Somewhat limited	Very limited	Moderately slow	Low
5	ARBOLES CLAY, 3 TO 12 PERCENT SLOPES								
		ARBOLES	80	> 72	None	Very limited	Very limited	Slow	Very high
50	PESCAR FINE SANDY LOAM								
		PESCAR	75	24-72	Frequent	Very limited	Very limited	Moderately rapid	Very low
51	PICANTE-ROCK OUTCROP COMPLEX, 10 TO 45 PERCENT SLOPES								
		PICANTE	50	> 72	None	Very limited	Very limited	Slow	Very high
		ROCK OUTCROP	25	> 72	None	Very limited	Very limited	Very slow	Very high
52	PINATA LOAM, 1 TO 12 PERCENT SLOPES								
		PINATA	80	> 72	None	Somewhat limited	Very limited	Slow	High
53	PINATA LOAM, 12 TO 40 PERCENT SLOPES								
		PINATA	80	> 72	None	Very limited	Very limited	Slow	Very high
55	PLOME FINE SANDY LOAM, 3 TO 12 PERCENT SLOPES								
		PLOME	80	> 72	None	Somewhat limited	Very limited	Moderate	Medium
56	PULPIT LOAM, 3 TO 12 PERCENT SLOPES								
		PULPIT	80	> 72	None	Very limited	Very limited	Slow	High
58	ROCK OUTCROP								
		ROCK OUTCROP	100	> 72	None	Very limited	Very limited	Very slow	Very high
59	SEDILLO GRAVELLY LOAM, 0 TO 3 PERCENT SLOPES								
		SEDILLO	80	> 72	None	Somewhat limited	Somewhat limited	Moderately slow	Medium
6	ARCHULETA LOAM, 12 TO 65 PERCENT SLOPES								
		ARCHULETA	80	> 72	None	Very limited	Very limited	Slow	Very high
60	SHALONA LOAM								
		SHALONA	80	> 72	None	Somewhat limited	Somewhat limited	Moderately slow	Medium
61	SHAWA VARIANT LOAM, 5 TO 20 PERCENT SLOPES								
		SHAWA VARIANT	80	> 72	None	Somewhat limited	Very limited	Moderately slow	Medium

Map Unit Symbol	Map Unit Name	Component Name	Percent of Map Unit	Depth to Seasonal High Water Table (inches)	Seasonal Flooding Frequency	Limitations for Buildings without Basements	Limitations for Sewage Lagoons	Permeability Class	Runoff Class
62	SILI CLAY LOAM, 1 TO 3 PERCENT SLOPES								
		SILI	80	> 72	None	Very limited	Somewhat limited	Slow	High
63	SILI CLAY LOAM, 3 TO 6 PERCENT SLOPES								
		SILI	80	> 72	None	Very limited	Somewhat limited	Slow	Very high
64	SIMPATICO LOAM								
		SIMPATICO	70	> 72	Rare	Very limited	Somewhat limited	Moderately slow	Medium
65	SYCLE FINE SANDY LOAM								
		SYCLE	85	> 72	None	Not limited	Very limited	Moderate	Low
66	TEFTON LOAM								
		TEFTON	70	30-72	Rare	Very limited	Very limited	Moderate	Low
67	UINTA LOAM, 5 TO 15 PERCENT SLOPES								
		UINTA	90	> 72	None	Somewhat limited	Very limited	Moderate	Medium
68	UINTA LOAM, 15 TO 60 PERCENT SLOPES								
		UINTA	85	> 72	None	Very limited	Very limited	Moderate	High
69	UMBARG LOAM								
		UMBARG	85	42-72	None	Somewhat limited	Somewhat limited	Moderately slow	Medium
7	ARCHULETA-SANCHEZ COMPLEX, 12 TO 65 PERCENT SLOPES								
		ARCHULETA	45	> 72	None	Very limited	Very limited	Slow	Very high
		SANCHEZ	30	> 72	None	Very limited	Very limited	Slow	Very high
70	USTIC TORRIORTHENTS-USTOLIC HAPLARGIDS COMPLEX, 12 TO 60								
		USTIC TORRIORTHENTS	50	> 72	None	Very limited	Very limited	Moderate	High
		USTOLIC HAPLARGIDS	30	> 72	None	Very limited	Very limited	Moderate	High
71	VALTO-ROCK OUTCROP COMPLEX, 12 TO 65 PERCENT SLOPES								
		VALTO	45	> 72	None	Very limited	Very limited	Slow	Very high
		ROCK OUTCROP	35	> 72	None	Very limited	Very limited	Very slow	Very high
72	VERNAL FINE SANDY LOAM, 1 TO 3 PERCENT SLOPES								
		VERNAL	85	> 72	None	Not limited	Very limited	Moderately slow	Medium

Map Unit Symbol	Map Unit Name	Component Name	Percent of Map Unit	Depth to Seasonal High Water Table (inches)	Seasonal Flooding Frequency	Limitations for Buildings without Basements	Limitations for Sewage Lagoons	Permeability Class	Runoff Class
73	VERNAL-SEDILLO COMPLEX, 3 TO 12 PERCENT SLOPES								
		VERNAL	45	> 72	None	Not limited	Very limited	Moderately slow	High
		SEDILLO	30	> 72	None	Somewhat limited	Very limited	Moderately slow	High
74	VOSBURG FINE SANDY LOAM, 3 TO 8 PERCENT SLOPES								
		VOSBURG	85	> 72	None	Not limited	Somewhat limited	Moderate	Medium
75	WITT LOAM, 1 TO 3 PERCENT SLOPES								
		WITT	90	> 72	None	Not limited	Somewhat limited	Moderately slow	Medium
76	WITT LOAM, 3 TO 8 PERCENT SLOPES								
		WITT	90	> 72	None	Not limited	Somewhat limited	Moderately slow	High
77	WITT LOAM, 3 TO 12 PERCENT SLOPES, ERODED								
		WITT, ERODED	60	> 72	None	Somewhat limited	Very limited	Moderately slow	High
78	YENLO-FLORITA SANDY LOAMS								
		YENLO	50	> 72	None	Not limited	Somewhat limited	Moderate	Low
		FLORITA	35	> 72	None	Not limited	Very limited	Moderately rapid	Low
79	ZAU STONY LOAM, 3 TO 9 PERCENT SLOPES								
		ZAU	80	> 72	None	Somewhat limited	Very limited	Very slow	Very high
8	BACA VARIANT LOAM, 3 TO 12 PERCENT SLOPES								
		BACA VARIANT	75	> 72	None	Somewhat limited	Very limited	Moderately slow	High
80	ZAU STONY LOAM, 9 TO 25 PERCENT SLOPES								
		ZAU	75	> 72	None	Very limited	Very limited	Very slow	Very high
81	ZYME CLAY LOAM, 3 TO 25 PERCENT SLOPES								
		ZYME	70	> 72	None	Very limited	Very limited	Slow	Very high
82	ZYME-ROCK OUTCROP COMPLEX, 12 TO 65 PERCENT SLOPES								
		ZYME	50	> 72	None	Very limited	Very limited	Slow	Very high
		ROCK OUTCROP	30	> 72	None	Very limited	Very limited	Very slow	Very high
9	BADLAND								
		BADLAND	90	> 72	None	Very limited	Very limited	Very slow	Very high